

DELTA 417R

PANEL PC

Fanless 17" Panel PC, Intel Atom x6425E, 8GB RAM, 256GB SSD, Windows 10 IoT

- Enclosure:
 - Front bezel: Die cast aluminum alloy
 - Rear: ABS
- Resistive Touchscreen
- IP66-rated front panel
- 2x 2.5 GbE LAN
- 2x RS-232, 1x isolated RS-422/485
- 2x USB 2.0, 2x USB 3.2
- 1x HDMI, 1x DisplayPort
- 1x Mic-in/Line-out



Properties



Certificates



Technical data

ELMATIC DELTA 417R

System	CPU	Intel Atom x6425E
	Frequency	2.00 GHz, up to 3.00 GHz
	Total Cores	4
	Total Threads	4
	Cache	1.5 MB
	Memory	1 × SODDR4 8GB industrial grade
	Storage	256GB M.2 2280 SATA industrial grade
	Network (LAN)	2 x 10/100/1000/2500 Mbps Ethernet (Intel i226)

Elmark Automatyka reserves the right to change the configuration without warning.

Physical Characteristics	I/O	2 x RS-232 1 x RS-422/485 with 1K VDC isolation 2 x USB 3.2 2 x USB 2.0 1 x Line-Out 1 x Mic-In 1 x HDMI 1 x DisplayPort 1 x TPM2.0
	Expansion	1 x M.2 2230 E Key slot for wireless card 1 x PCIe x1 (default) 1 x PCI (optional) 1 x Cfast card (optional)
	Dimensions	437 x 357 x 56.5 mm Panel Cutout Dimensions: 427 x 347 mm
	Weight	7.8 kg
	Enclosure	Front bezel: Die cast aluminum alloy Rear: ABS
Power Consumption	Input Voltage	9 ~ 32 VDC
OS Support	Windows	Windows 10 IoT LTSC
	Display Type	17" TFT LED panel
	Max. Resolution	1280 x 1024
LCD	Viewing Angle	80 (left), 80 (right), 60 (up), 80 (down)
	Luminance (cd/m ²)	350
	Contrast Ratio	800
	Backlight Lifetime	50,000 hr (min.)
Touchscreen	Touch Type	5-wire analog resistive
	Light Transmission	81+/-3%
	Controller	USB interface
	Operating Temperature	-20 ~ 60 °C
Environment	Storage Temperature	-40 ~ 60 °C
	Relative Humidity	95% @ 40 °C (Non-Condensing)
	Shock	Operating 10 G peak acceleration (11 ms duration), follow IEC 60068-2-27
	Vibration	Operating Random Vibration Test 5 ~ 500Hz, 2Grms @with SSD, follow IEC 60068-2-64
	EMC	CE, FCC Class B, EN 61000-6-2, BSMI, VCCI, UKCA
	Safety	CB, UL, CCC, UKCA
	Front Panel Protection	IP66 compliant

Elmark Automatyka reserves the right to change the configuration without warning.


Elmark Automatyka S.A.

ul. Bukowińska 22 lok. 1B, 02-703 Warszawa

www.elmark.com.pl, e-mail: elmark@elmark.com.pl, tel.: (+48) 22-773-79-37


TAX ID: 5252072585, KRS: 0000803828, Sąd Rejonowy dla M.St. W-wy, XIII Wydział Gosp. KRS, Share capital 600.000 zł, fully paid-up.

Dimensions [mm]



Inputs/Outputs

I/O View



Elmark Automatyka reserves the right to change the configuration without warning.

Elmark Automatyka S.A.

ul. Bukowińska 22 lok. 1B, 02-703 Warszawa

www.elmark.com.pl, e-mail: elmark@elmark.com.pl, tel.: (+48) 22-773-79-37

TAX ID: 5252072585, KRS: 0000803828, Sqd Rejonowy dla M.St. W-wy, XIII Wydział Gosp. KRS, Share capital 600.000 zł, fully paid-up.

Packing list

ELMATIC DELTA 417R Unit

Power cable (type E/F)

Windows license

CE Declaration

Ordering information

Part Number	Description
-------------	-------------

ELMATIC DELTA 417R

PanelPC, 17", x6425E, 8GB, 256GB, Win10IoT, rez.

Accessories

Part Number	Description
-------------	-------------

FSP096-AHAN3

Desktop PSU

PPC-ARM-A03

ARM VESA Standard

PPC-174T-WL-MTE

Wall mount kit

PPC-Stand-A1E

Stand for ELMATIC DELTA 417R

Elmark Automatyka reserves the right to change the configuration without warning.

Elmark Automatyka S.A.

ul. Bukowińska 22 lok. 1B, 02-703 Warszawa

www.elmark.com.pl, e-mail: elmark@elmark.com.pl, tel.: (+48) 22-773-79-37

TAX ID: 5252072585, KRS: 0000803828, Sąd Rejonowy dla M.St. W-wy, XIII Wydział Gosp. KRS, Share capital 600.000 zł, fully paid-up.